

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/19/2017

Reviewed on 10/19/2017

Page 1/10

#### 1 Identification

#### · Product Identifier

- · Trade name: Craft Meister Alkaline Brewery Wash
- · Relevant identified uses of the substance or mixture and uses advised against:
- · Product Description Wash
- · Details of the Supplier of the Safety Data Sheet:
- *Manufacturer/Supplier:* National Chemicals, Inc. PO Box 506, Lewiston, MN 55952 Ph: 800-533- 0027 / 507-454- 5640 info@NationalChemicals.com
- · Emergency telephone number: CHEMTREC 1-800-424-9300

#### 2 Hazard(s) Identification

#### · Classification of the substance or mixture:

GHS05 Corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.



Eye Irrit. 2AH319Causes serious eye irritation.STOT SE 3H335May cause respiratory irritation.

- · Label elements:
- GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms:



· Signal word: Danger

- · Hazard-determining components of labeling:
- Disodium Metasilicate

Trisodium Orthophosphate

#### Hazard statements:

- H314 Causes severe skin burns and eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- Precautionary statements:
- P260 Do not breathe dusts or mists.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/19/2017

#### Reviewed on 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.		
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/		
	shower.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if		
	present and easy to do. Continue rinsing.	
P312	Call a poison center/doctor if you feel unwell.	
P321	Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P363	Wash contaminated clothing before reuse.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P501	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	

#### · Unknown acute toxicity:

This value refers to knowledge of known, established toxicological or ecotoxicological values.

- 1 % of the mixture consists of component(s) of unknown toxicity.
- · Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- NFPA ratings (scale 0 4)

Health = 2
Fire = 0
Reactivity =

· HMIS-ratings (scale 0 - 4)



Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

= 0

- Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:		
497-19-8	Sodium carbonate	40-60%
	🚸 Eye Irrit. 2A, H319	
6834-92-0	Disodium Metasilicate	25-50%
	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; STOT SE 3, H335	
7601-54-9	Trisodium Orthophosphate	≤2.5%
	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
Additional information		

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.



· Description of first aid measures:

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Remove to fresh air.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/19/2017

Reviewed on 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

If easy to do so, remove contact lenses if worn.

• After swallowing:

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Do not induce vomiting without medical advice.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

#### 5 Fire-Fighting Measures

- Extinguishing media:
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters:
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

#### 6 Accidental Release Measures

- *Personal precautions, protective equipment and emergency procedures:* Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
497-19-8	Sodium carbonate	7.6 mg/m <sup>3</sup>
6834-92-0	Disodium Metasilicate	3.8 mg/m <sup>3</sup>
7758-29-4	Pentasodium triphosphate	0.61 mg/m³
7722-88-5	Tetrasodium Pyrophosphate	15 mg/m³
· PAC-2:		
497-19-8	Sodium carbonate	83 mg/m³
6834-92-0	Disodium Metasilicate	42 mg/m <sup>3</sup>
7758-29-4	Pentasodium triphosphate	6.8 mg/m³
		(Contd. on page 4



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

#### Issue date 10/19/2017

Page 4/10

#### Trade name: Craft Meister Alkaline Brewery Wash

7722-88-5	Tetrasodium Pyrophosphate	130 mg/m³
• PAC-3:		
497-19-8	Sodium carbonate	500 mg/m³
6834-92-0	Disodium Metasilicate	250 mg/m <sup>3</sup>
7758-29-4	Pentasodium triphosphate	620 mg/m³
7722-88-5	Tetrasodium Pyrophosphate	790 mg/m³

#### 7 Handling and Storage

#### · Handling

 Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about protection against explosions and fires: No special measures required.

- · Conditions for safe storage, including any incompatibilities:
- · Storage
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- Information about storage in one common storage facility: Do not store together with acids.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s): No further relevant information available.

#### 8 Exposure Controls/Personal Protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- Components with occupational exposure limits:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 7601-54-9 Trisodium Orthophosphate

WEEL Short-term value: 5 mg/m<sup>3</sup>

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

- Exposure controls:
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective aloves



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 5/10

Issue date 10/19/2017

#### Reviewed on 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Select glove material based on penetration times, rates of diffusion and degradation.

- Material of gloves:
- Solvent Resistant

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material: Not applicable.
- Eye protection:



Goggles recommended

#### 9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information

· General Information · Appearance:	
Form: Color: · Odor: · Odor threshold:	Powder White Odorless Not determined.
· pH-value:	Not applicable.
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Not determined. Not determined.
· Flash point:	None
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	Not applicable
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Product does not present an explosion hazard.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	Not determined. Not determined.
· Vapor pressure:	Not determined.
<ul> <li>Density:</li> <li>Relative density:</li> <li>Vapor density:</li> <li>Evaporation rate:</li> </ul>	Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with: Water:</li> </ul>	Not miscible or difficult to mix.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 6/10

#### Issue date 10/19/2017

Reviewed on 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.00 %

• Other information:

0.00 % No further relevant information available.

#### 10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Exposure to moisture or moist air. Temperatures above 150°F (65 °C).
- · Incompatible materials: Strong acids, strong bases

#### 1 Toxicological Information

- · Information on toxicological effects:
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

497-19-8 Sodium carbonate

Oral LD50 4,090 mg/kg (Rat)

Inhalative LC50/96 hours 300 mg/l (Fathead Minnow)

6834-92-0 Disodium Metasilicate

Oral LD50 1,280 mg/kg (Rat)

#### Primary irritant effect:

• On the skin:

Corrosive effect on skin and mucous membranes.

Corrosive to skin and mucous membranes.

#### On the eye: Irritating effect.

Corrosive effect.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):	
None of the ingredients are listed.	
· NTP (National Toxicology Program):	
None of the ingredients are listed.	

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/19/2017

Reviewed on 10/19/2017

Page 7/10

#### Trade name: Craft Meister Alkaline Brewery Wash

#### · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

#### 12 Ecological Information

- · Toxicity:
- Aquatic toxicity:
- 497-19-8 Sodium carbonate
- EC50 227 mg/l (Daphnia)

#### 6834-92-0 Disodium Metasilicate

- EC50 247 mg/l (Water flea)
- Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · *Bioaccumulative potential:* No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

#### **13 Disposal Considerations**

#### · Waste treatment methods:

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

#### 4 Transport Information

<ul> <li>· UN-Number:</li> <li>· DOT, ADR/ADN, ADN, IMDG, IATA</li> <li>· UN proper shipping name:</li> <li>· DOT, ADR/ADN, ADN, IMDG, IATA</li> <li>· Transport hazard class(es):</li> </ul>	Non-Regulated Material Non-Regulated Material	
· DOT, ADR/ADN, ADN, IMDG, IATA · Class: · Packing group:	Non-Regulated Material	
· DOT, ADR/ADN, IMDG, IATA	Non-Regulated Material	
<ul> <li>Environmental hazards:</li> </ul>	Not applicable.	
<ul> <li>Special precautions for user:</li> </ul>	Not applicable.	
<ul> <li>Transport in bulk according to Annex II of</li> </ul>		
MARPOL73/78 and the IBC Code:	Not applicable.	



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 8/10

Reviewed on 10/19/2017

Issue date 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

• UN "Model Regulation":	Non-Regulated Material

## 15 Regulatory Information

# Safety, health and environmental regulations/legislation specific for the substance or mixture: SARA (Superfund Amendments and Reauthorization): Section 355 (extremely hazardous substances):

7601-54-9 Trisodium Orthophosphate

- · Section 313 (Specific toxic chemical listings):
- 7601-54-9 Trisodium Orthophosphate

7758-29-4 Pentasodium triphosphate

- TSCA (Toxic Substances Control Act):
- All ingredients are listed or exempt from listing.
- · TSCA new (21st Century Act) (Substances not listed)
- California Proposition 65:
- Chemicals known to cause cancer:

None of the ingredients are listed.

 $\cdot$  Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

New Jersey Right-to-Know List:

7601-54-9 Trisodium Orthophosphate

7722-88-5 Tetrasodium Pyrophosphate

· New Jersey Special Hazardous Substance List:

None of the ingredients are listed.

· Pennsylvania Right-to-Know List:

10124-56-8 Sodium Hexametaphosphate

7601-54-9 Trisodium Orthophosphate 7758-29-4 Pentasodium triphosphate

- 7722-88-5 Tetrasodium Pyrophosphate
- Pennsylvania Special Hazardous Substance List:
- 10124-56-8 Sodium Hexametaphosphate
- 7601-54-9 Trisodium Orthophosphate

7758-29-4 Pentasodium triphosphate

### · Carcinogenic categories:

• EPA (Environmental Protection Agency):

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

Е

Е

Е



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/19/2017

Reviewed on 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

- NIOSH-Ca (National Institute for Occupational Safety and Health):
- None of the ingredients are listed.
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms:



· Signal word: Danger

- Hazard-determining components of labeling:
- Disodium Metasilicate
- Trisodium Orthophosphate

#### · Hazard statements:

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements:

- P260 Do not breathe dusts or mists.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### • National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision: 10/19/2017 / 4

Page 9/10



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 10/19/2017

Reviewed on 10/19/2017

#### Trade name: Craft Meister Alkaline Brewery Wash

#### • Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety & Health Administration TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 \* Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106